

LED Miniature Stop Light



Features:

- Directly interchangeable with existing filament units
- No design changes at site required
- Fits directly onto existing post
- Not affected by variations in supply voltage
- Supply Voltage 110Vac/120 Vdc

“Phone Crossing Operator” and “Proceed with Caution” versions available.

Benefits:

- LED technology gives long service life
- Improved visibility
- LED light source for increased safety and reliability
- Reduced maintenance costs

Contact for technical advice

Telephone: +44 (0) 1270 847600

Facsimile: +44 (0) 1270 847601

e-mail: technicalsupport@unipartrail.com

PADS No	Dorman Part No	Description
086/009260	MSLH2/RG/1/P/G	Miniature Stop Light Head, 2 Aspect, Red, Green, 1 110Vac/120Vdc, Proved, Ground (Phone Crossing Operator) 107
086/009261	MSLC2/RG/1/P/G	Miniature Stop Light Head, 2 Aspect, Red, Green 1 110Vac/120Vdc, Proved, Ground (Proceed with Caution) 108

Compliances

Network Rail RT/E/S10110

Approvals

Unrestricted Network Rail Certificate No:

Complete Signal
Modules

PA05/02619
PA05/01133

Key Specifications

Operating Temperature Range	-25°C to +40°C
Nominal Operating Voltage	110Vac/120Vdc
Operating Voltage Range	Max 121Vac Min 88Vac Max 145Vdc Min 88Vdc
Nominal Operating Current	300mA @ 110Vac per light source

Current Proving

Relay Based Interlocking BR941A

Mounting Arrangements

Mounting Post 60.3mm Dia
Post Drawing BRS – SM 91

Sealing of LED Modules IP 65

Sealing of Housing IP 54

Weight 17kg

Available from:

Unipart Rail, Gresty Road, Crewe, Cheshire, CW2 6EH, UK

T +44 (0) 1270 847 600 **F** +44 (0) 1270 847601