

Cyclon Point End Switching Battery

Sealed lead acid cells requiring no separate battery room or racking



Cat N° 0054/003080

- 120VDC 5Ah Cyclon sealed lead acid
- Twin output terminals 30 Amps, 3,000 VDC colour coded fully insulated binding posts (screw terminals)
- Maximum pulse current 250 Amps
- Minimum continuous current 30 Amps
- Can be float charged at 2.35V/cell \pm 1%
- 15 year float life at 20°C
- Dimensions 100 mm height x 470 mm width x 290 mm depth

42Ah (for up to 30 points operations) and 86Ah (for up to 50 points operations) are now available and awaiting Railtrack approval

Insulated clear viewing lid with no access to inter-cell links

- No maintenance requirement
- Replaces NiCad and Plante batteries
- Easily hand portable
- Compact with excellent power to volume ratio
- Storage life two years
- Sealed non-spillable design
- Can be mounted in any orientation




Contact for technical advice

Telephone: +44 (0) 1270 847708

Facsimile: +44 (0) 1270 847721

e-mail: technicalsupport@unipartrail.com

Other items available from Unipart Rail

 <p>Cat N° 0054/010764</p>	2v 25Ah Cyclon BC Cell	Cat N° 0054/010764
	Intercell Strap Connector Cyclon Cells – Short	Cat N° 0054/010765
	Intercell Strap Connector Cyclon Cells - Long	Cat N° 0054/010766

Items available from Unipart Rail on special order

2V 2.5Ah Cyclon D Cell	Cat N° 0054/010696
2V 4.5Ah Cyclon DT Cell	Cat N° 0054/010761
2V 5Ah Cyclon X Cell	Cat N° 0054/010697
2V 8Ah Cyclon E Cell	Cat N° 0054/010762
2V 12.5Ah Cyclon J Cell	Cat N° 0054/010763

Available from:

Unipart Rail, Gresty Road, Crewe, Cheshire, CW2 6EH, UK

T +44 (0) 1270 847 600 **F** +44 (0) 1270 847601